

Highlights

- **FAST:** The PR-TB-N-3000S has a print speed of 30rpm (150mm/sec)
- **RELIABLE:** reliable guillotine cutter.
- **INTEROPERABILITY:** Available in serial, parallel, ethernet and USB. Works in Windows XP, Vista, Linux, Mac OSX, OPOS, JavaPOS, ESC/POS
- Drop in paper loading
- Epson Emulation



PR-TB-N-3000S

PointOS Professional PR-TB-N-3000S Touch Data Sheet

Features Hardware	Fast: 30 receipts per minute (30RPM), 150 mm/sec) "Drop-in & Print" Clamshell Design Reliable Guillotine Cutter Small Footprint Two Color Print Capable Swappable Communication Interface Horizontal & Vertical Use Recessed Cable Connections ESC/POS® emulation supported	
Features Software	Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration Setup Utility Ethernet Interface Setup Utility Virtual Serial Port for legacy applications	
Connectivity	25-pin serial Parallel USB Powered USB Ethernet Virtual Serial Port to USB Virtual Serial Port to Ethernet	
Drivers	Windows 98, ME NT 4.0 WEPOS 2000, XP CE XP Embedded VISTA	OPOS Java POS Linux CUPS Mac OSX CUPS
What's included	Setup Sheets Wall Mount Bracket 58mm Paper Guide Power Switch Cover Start up Paper Roll Vertical Kit	
Optional Accesories	Splash Proof Cover (SPC-T100) Integrated Buzzer (BU01-24-A) Vertical Stand (VS-T650)	
Technical Specifications	Print Method : Direct Thermal Print Speed : Print Speed: 30 Receipts per Minute (30RPM, 150mm/sec) Paper Width : 80mm / 58mm Paper Thickness : 0.065 – 0.085mm Paper Diameter : Max 83mm Emulation : Star Line Mode, ESC/POS®	Power : DC24V External Power Supply Resolution: 203 dpi MCBF: 60 Million Lines Cutter: 1 million cuts Dimensions: W=5.6inn H=5.2in, D=8in